

FallTech 8123BQC FT-One 3D Belted Harness

Specification Sheet | SKU 8123BQC | FallTech

Features

- Comfort Legs® lateral leg strap construction greatly improves mobility and comfort.
- New Modular Belt System™ allows for custom configuration of tool bag and pouch positions for ease of use, comfort, and efficiency.
- ArrowGrip® dorsal D-ring plate and new slip-resistant connectors minimize slippage for maximum comfort and minimal adjustment throughout the day.
- Waist belt features four ANSI/ISEA 121-compliant tool tether anchor attachments, rated at five pounds each.
- Industry-exclusive shoulder pad material is abrasion resistant to mitigate excess wear and keep the harness in service longer.
- Advanced gel padding material disperses harness loads, eliminating hot spots and pressure points for all-day comfort.



Technical Specifications

Type	Belted Full Body Harness
SKU	8123BQC
Family	FT-One
D-Rings	3 (Dorsal and Hip)
Closures	Quick-connect Legs and Chest
Webbing	Polyester
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2014; OSHA 1926.502 and 1910.140; CSA Z259.10-2018
Available Configurations	8123BQCXS (XS), 8123BQCS (Small), 8123BQCM (Medium), 8123BQCL (Large), 8123BQCXL (XL), 8123BQC2X (2X), 8123BQC3X (3X)
Warranty	FallTech 2-year manufacturer warranty, honored through Fall Protection Distributors

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.