

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

B0502189

Declaration Date

5/2/2023

Tested Item #

8124B3DQCM

FT-One FBH 3D Standard Non-Belted, Medium, QC
Legs and Chest

Additional Items Conforming Under this Declaration:

8124B3DQCXS 8124B3DQCXL

8124B3DQCS 8124B3DQC2X

8124B3DQCL 8124B3DQC3X

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with
the requirements of the following product standard(s):

ANSI Z359.11-2021

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

Level 3

Level 1: FallTech Lab
Outside the Scope of
ISO/IEC Standard 17025:2005

Level 2: FallTech Lab
Within the Scope of
ISO/IEC Standard 17025:2005

Level 3: Independent 3rd Party Lab
accredited to
ISO/IEC Standard 17025:2005

Supporting
Documentation

PC-2821

Authorized Signature

Name

Zachary Winters

Title

Engineering Manager

Date

5/2/2023



International Accreditation Service, Inc
3060 Saturn St, Ste 100
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594
ISO/IEC 17025:2017

Alexander Andrew Inc dba FallTech

FallTech Test Report

Test Report No.	PC-2821	Rpt. Date	5/1/2023	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Zachary Winters	Test Specification(s)		ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6			
Part No.	8124B3DQCM	Part No. Revision			A		
Part Description	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest						
Test Request No.	PC-2821	Date Complete			5/1/2023		
Test Operator(s)	Yesbet Sierra / Jay Sponholz						

Material/Sample Identification

Sample ID	Description
5666142	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest
5664952	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest
5666127	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest
5664951	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest
5664957	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest
5666141	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest
5666129	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest
5666134	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest
5666140	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest
5666144	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest
5666136	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest
5666138	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest
5666141	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest
5664957	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest
5664951	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest

Test Summary

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf \geq 1 Minute	3635.1 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.23"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf \geq 1 Minute	3643.5 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.25"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf \geq 1 Minute	3649.5 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.20"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass

FallTech Test Report

Test Report No.	PC-2821	Rpt. Date	5/1/2023	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Zachary Winters	Test Specification(s)	ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6				
Part No.	8124B3DQCM	Part No. Revision	A				
Part Description	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest						
Test Request No.	PC-2821	Date Complete	5/1/2023				

Test Summary Continued

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf \geq 1 Minute	3629.9 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf \geq 1 Minute	3648.2 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf \geq 1 Minute	3637.7 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load \geq 3600 Lbf	4440.7 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest \leq 30°	3.8°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	11.0"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load \geq 3600 Lbf	4524.1 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest \leq 30°	3.3°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	11.4"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load \geq 3600 Lbf	4511.1 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest \leq 30°	1.8°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	11.0"	Pass

FallTech Test Report

Test Report No.	PC-2821	Rpt. Date	5/1/2023	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Zachary Winters	Test Specification(s)	ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6				
Part No.	8124B3DQCM	Part No. Revision	A				
Part Description	FT-One FBH 3D Standard Non-Belted, Medium, QC Legs and Chest						
Test Request No.	PC-2821	Date Complete	5/1/2023				

Test Summary Continued

Test Specification	Test Criteria	Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact \geq 3,600 Lbf or 72" Free Fall 2928.4 Lbf	72" Free fall 2928.4 Lbf Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release Pass
	Post Drop Angle	Angle at Rest \leq 30°	5.6° Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact \geq 3,600 Lbf or 72" Free Fall 2396.7 Lbf	72" Free fall 2396.7 Lbf Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release Pass
	Post Drop Angle	Angle at Rest \leq 30°	3.6° Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact \geq 3,600 Lbf or 72" Free Fall 2762.7 Lbf	72" Free fall 2762.7 Lbf Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release Pass
	Post Drop Angle	Angle at Rest \leq 30°	8.7° Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed Pass

Conclusion

Based upon the samples provided to the Lab:
 FallTech P/N 8124B3DQCM Rev. A meets the requirements of ANSI Z359.11-2021

Report Signatories and Approval

Lab Quality Manager		Date	5/1/2023
---------------------	---	------	----------