

FallTech 8124B3DQC FT-One 3D Harness, Quick Connect Adjustments

Specification Sheet | SKU 8124B3DQC | FallTech

Features

- Comfort Legs® lateral leg strap construction greatly improves mobility and comfort.
- ArrowGrip® dorsal D-ring plate and new slip-resistant connectors minimize slippage for maximum comfort and minimal adjustment throughout the day.
- Industry-exclusive shoulder pad material is abrasion resistant to mitigate excess wear and keep the harness in service longer.
- Advanced gel padding material disperses harness loads, eliminating hot spots and pressure points for all-day comfort.
- Durable lanyard keeper design improves versatility and reusability while maintaining ANSI compliance.
- Includes fully adjustable suspension trauma relief system.



Technical Specifications

Type	Non-Belted Full Body Harness
SKU	8124B3DQC
Family	FT-One
D-Rings	3 (Dorsal and Hip)
Closures	Quick-connect Legs and Chest
Webbing	Polyester
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2021; OSHA 1926.502 and 1910.140; CSA Z259.10-2018
Available Configurations	8124B3DQCXS (XS), 8124B3DQCS (Small), 8124B3DQCM (Medium), 8124B3DQCL (Large), 8124B3DQCXL (XL), 8124B3DQC2X (2X), 8124B3DQC3X (3X)
Warranty	FallTech 2-year manufacturer warranty, honored through Fall Protection Distributors

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.