

FallTech 8149 Vertical Lifeline, 50 ft, Blue Polyester

Part Number(s): 8149 | Brand: FallTech | Product Specification Sheet

Features

- Constructed with construction-grade 5/8" copolymer 3-strand twisted rope
- Steel thimble and splice-protecting shrink tube are included for lasting durability
- Includes alloy steel snap hook for anchorage connection
- Back-spliced trailing end is ideally suited for pairing with hinged arresters and adjusters
- Complies with ANSI Z359.15-2014



Specifications

Description	Back-splice rope end
Static Strength	5,000 lbs. Min.
ANSI User Capacity	130 to 310 lbs. Max.
OSHA User Capacity	130 to 310 lbs. Max.
Rope	3-strand twisted copolymer; 5,000 lbs. Min.
Connector	Plated alloy steel; 5,000 lbs. Min. static strength with 3,600 lbs. gate strength
Thimble	Plated Carbon Steel
Unit Weight	5.8 lb
Relevant Standards	ANSI Z359.15-2014; OSHA 1926.502 and 1910.66

Distributed by Fall Protection Distributors, LLC, an authorized FallTech dealer. standingseamroofanchor.com | 863-703-4522.
Specifications from FallTech published product data. Always follow the FallTech instruction manual.