

FallTech Vertical Lifeline, 75 to 500 ft, 5/8 in Rope

Part Number(s): 8175, 81505, 820020, 8150250, 8150300, 8150350, 8150500 | Brand: FallTech | Product Specification Sheet

Features

- Constructed with 5/8" low-stretch 3-strand twisted rope
- Premium polyester blend reduces kinking and hockling.
- Steel thimble and splice-protecting shrink tube are included for lasting durability
- Includes alloy steel snap hook for anchorage connection
- Back-spliced trailing end is ideally suited for pairing with hinged arresters and adjusters
- Complies with ANSI Z359.15-2014



Specifications

Description	Back-splice rope end
Static Strength	5,000 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 310 lb max.
Rope	3-strand twisted polyester blend; 5,000 lb min.
Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Thimble	Plated carbon steel
Unit Weight	9.2 lb
Relevant Standards	ANSI Z359.15-2014; OSHA 1926.502 and 1910.66; CSA Z259.2.5-2017

Distributed by Fall Protection Distributors, LLC, an authorized FallTech dealer. standingseamroofanchor.com | 863-703-4522.
Specifications from FallTech published product data. Always follow the FallTech instruction manual.