

FallTech WrapTech Adjustable Restraint Lanyard, 4 to 6 ft

Part Number(s): 8209WT | Brand: FallTech | Product Specification Sheet

Features

- Kevlar construction is ideally suited for hot-work welding applications
- Includes alloy steel snap hooks for harness and anchorage connections
- Integrated alloy steel buckle facilitates simple user adjustment to desired length
- Restraint lanyard affectively restricts users from reaching identified fall hazards
- Meets OSHA 1926.502 and 1910.66 Regulations



Specifications

Description	Steel Snap Hook
Static Strength	5,000 lbs. Min.
ANSI User Capacity	130 to 310 lbs. Max.
OSHA User Capacity	130 to 425 lbs. Max.
Webbing	Kevlar; 5,000 lbs. Min. Static Strength
Connectors	Plated alloy steel; 5,000 lbs. Min. static strength with 3,600 lbs. gate strength
Adjuster	Plated Alloy Steel; 3,375 lbs. Min. Static Strength
Unit Weight	2 lb
Relevant Standards	OSHA 1926.502 and 1910.66

Distributed by Fall Protection Distributors, LLC, an authorized FallTech dealer. standingseamroofanchor.com | 863-703-4522.
Specifications from FallTech published product data. Always follow the FallTech instruction manual.