

FallTech ElasTech Shock Absorbing Lanyard, 6 ft Single

Part Number(s): 8240, 8240A, 82403, 82403A, 824032D, 82403L2D | Brand: FallTech | Product Specification Sheet

Features

- Elastic leg construction provides variable working length from 4-1/2' to 6' and helps reduce tripping hazards
- High-modulus internal elastic effortlessly expands and contracts with user's movement and retains its elasticity longer than woven materials.
- Full-length internal energy absorber delivers flexible low-profile user comfort compared to traditional pack-style lanyards
- Durable tubular polyester webbing throughout resists abrasion and UV degradation
- Includes alloy steel snap hooks for harness and anchorage connections
- Complies with ANSI Z359.13-2013



Specifications

Description	Steel Snap Hook
Static Strength	5,000 lb min.
ANSI Lanyard Class	6' free fall
Max. Arrest Distance	48"
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
Webbing	Polyester; 5,000 lb min. static strength
Energy Absorber	Polyester POY
Connectors	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Unit Weight	2 lb
Relevant Standards	ANSI Z359.13-2013; OSHA 1926.502 and 1910.66

Distributed by Fall Protection Distributors, LLC, an authorized FallTech dealer. standingseamroofanchor.com | 863-703-4522.

Specifications from FallTech published product data. Always follow the FallTech instruction manual.