

FallTech ElasTech Shock Absorbing Lanyard, 6 ft Y-Leg

Part Number(s): 8240Y, 8240Y3, 8240Y32D, 8240Y3A | Brand: FallTech | Product Specification Sheet

Features

- Elastic leg construction provides variable working length from 4-1/2' to 6' and helps reduce tripping hazards
- High-modulus internal elastic effortlessly expands and contracts with user's movement and retains its elasticity longer than woven materials.
- Full-length internal energy absorber delivers flexible low-profile user comfort compared to traditional pack-style lanyards
- Durable tubular polyester webbing throughout resists abrasion and UV degradation
- Includes alloy steel snap hooks for harness attachment and anchorage connections
- Double-leg design facilitates 100% tie-off
- Meets OSHA 1926.502 and 1910.66 Regulations



Specifications

Description	Steel Snap Hooks
Static Strength	5,000 lb min.
Max. Arrest Distance	48"
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
OSHA User Capacity	130 to 310 lb max.
Webbing	Polyester; 5,000 lb min. static strength
Energy Absorber	Polyester POY
Connectors	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Unit Weight	4 lb
Relevant Standards	OSHA 1926.502 and 1910.66

Distributed by Fall Protection Distributors, LLC, an authorized FallTech dealer. standingseamroofanchor.com | 863-703-4522.
Specifications from FallTech published product data. Always follow the FallTech instruction manual.