

FallTech WrapTech Lanyard, 6 ft Single, 5k Carabiner

Part Number(s): 8241 | Brand: FallTech | Product Specification Sheet

Features

- Jacketed double-layer polyester webbing provides tie-back abrasion resistance
- Energy absorber features ViewPack cover with inspection window and WrapPack label protection.
- Wrap-around anchorage connection eliminates the need for a separate tie-off anchor point
- Includes alloy steel snap hook for harness attachment and 5k carabiner for tie-back anchorage
- Complies with ANSI Z359.13-2013



Specifications

Description	Steel 5k Carabiner
Static Strength	5,000 lb min.
ANSI Lanyard Class	6' free fall
Max. Arrest Distance	48"
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
Webbing	Polyester; 5,000 lb min. static strength
Energy Absorber	Polyester tear-away
Snap Hook	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Carabiner	Plated alloy steel; 5,000 lb min. static strength with 5,000 lb gate strength
Unit Weight	2.5 lb
Relevant Standards	ANSI Z359.13-2013; OSHA 1926.502 and 1910.66

Distributed by Fall Protection Distributors, LLC, an authorized FallTech dealer. standingseamroofanchor.com | 863-703-4522.

Specifications from FallTech published product data. Always follow the FallTech instruction manual.