

FallTech Arc Flash Adjustable Y-Leg EAL, 6 ft

Part Number(s): 8242Y3AFADJ, 8242Y3AFADJB, 8242Y3AFADJC | Brand: FallTech | Product Specification Sheet

Features

- Features Kevlar leg webbing throughout
- Includes pliable Soft Pack energy absorber with Nomex cover.
- Includes alloy steel snap hook for harness attachment and rebar hooks for anchorage connections
- Double-leg design facilitates 100% tie-off
- Rebar hooks feature transverse load rated gates
- Complies with ANSI Z359.13-2013 and ASTM F887-13



Specifications

Description	Steel Rebar Hooks
Static Strength	5,000 lb min.
ANSI Lanyard Class	6' free fall
Max. Arrest Distance	48"
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
Webbing	Kevlar; 5,000 lb min. static strength
Energy Absorber	Polyester tear-away
Connectors	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Choke-loop	Kevlar Webbing; 5,000 lbs. Min. Static Strength
Unit Weight	6.5 lb
Relevant Standards	ANSI Z359.13-2013; OSHA 1926.502 and 1910.66; ASTM F887

Distributed by Fall Protection Distributors, LLC, an authorized FallTech dealer. standingseamroofanchor.com | 863-703-4522.

Specifications from FallTech published product data. Always follow the FallTech instruction manual.