

# FallTech Arc Flash Energy Absorbing Lanyard, 6 ft Single

Specification Sheet | SKU 8242AFX | FallTech

## Features

- Features Kevlar leg webbing throughout.
- Includes pliable Soft Pack energy absorber with Nomex cover.
- Includes alloy steel snap hooks for harness attachment and anchorage connections.
- Complies with ANSI Z359.13-2013 and ASTM F887-13.



## Technical Specifications

|                                 |  |
|---------------------------------|--|
| <b>Type</b>                     | External Energy Absorbing Lanyard  |
| <b>SKU</b>                      | 8242AFX  |
| <b>Static Strength</b>          | 5,000 lb min.  |
| <b>ANSI Lanyard Class</b>       | 6' free fall   |
| <b>Max. Arrest Distance</b>     | 48"  |
| <b>Avg. Arrest Force</b>        | 900 lb   |
| <b>Max. Arrest Force</b>        | 1,800 lb   |
| <b>Webbing</b>                  | Kevlar; 5,000 lb min. static strength  |
| <b>Energy Absorber</b>          | Polyester tear-away  |
| <b>Connectors</b>               | Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength  |
| <b>Available Configurations</b> | 8242AF (Snap Hooks), 8242L (Web Loop), 8242LB (Loop and 5k Carabiner), 82426 (Aluminum CE Carabiner), 8242AFD (5k Carabiner, Dielectric) |
| <b>Standards</b>                | ANSI Z359.13-2013; OSHA 1926.502 and 1910.66; ASTM F887  |
| <b>Warranty</b>                 | FallTech 2-year limited warranty against defects in materials and workmanship  |

Fall Protection Distributors, LLC | [standingseamroofanchor.com](http://standingseamroofanchor.com) | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.