

FallTech 8242Y3 / C8242Y3

6' WeldTech Y-Leg 100% Tie-Off Lanyard, Rebar Hooks



Models	8242Y3 (ANSI Z359.13-2013) · C8242Y3 (CSA Z259.11-17)
Type	Double-leg 100% tie-off welding EAL, 6 ft, rebar hooks
Webbing	1 in Kevlar leg webbing w/ Nomex absorber cover, 5,000 lb min static
Energy absorber	Softpack energy absorber with Nomex cover; Kevlar leg webbing for spatter/burn resistance
Harness end	Alloy steel snap hook (harness)
Anchorage end	Two legs, each w/ transverse-load-rated steel rebar hook
Connector strength	5,000 lb min static, 3,600 lb gate
Capacity	350 lb max combined weight
Max free fall	6 ft (1.8 m)
Max absorber deployment	4.5 ft (1.4 m)
Min required fall clearance	18 ft (5.5 m) overhead, worst case
Standards	ANSI Z359.13-2013; CSA Z259.11-17; OSHA 1926.502 & 1910.66
UPC	848013088987 (8242Y3) · 848013067159 (C8242Y3)
Warranty	FallTech 2-year limited warranty

Distributed by Fall Protection Distributors, LLC • Call 863-703-4522 • Specs from FallTech manuals MSAL01ALX (ANSI) + CMSAL01 (CSA); WeldTech DoC C0616039 / CC0320006; subject to change without notice.