

FallTech WeldTech Internal Lanyard, 6 ft Single

Part Number(s): 8243, 82433 | Brand: FallTech | Product Specification Sheet

Features

- Low-profile design combines internal tubular polyester webbing with a tubular Nomex cover
- Features full-length internal energy absorber and visual fall indicator
- Nomex web jacket delivers excellent burn and spatter resistance
- Includes alloy steel snap hook for harness attachment and rebar hook for anchorage connection
- Meets OSHA 1926.502 and 1910.66 Regulations



Specifications

Description	Steel Snap Hook
Static Strength	5,000 lb min.
Max. Arrest Distance	48"
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
OSHA User Capacity	130 to 310 lb max.
Webbing	Polyester; 5,000 lb min. static strength
Leg Jacket	Tubular Nomex
Energy Absorber	Polyester tear-away
Connectors	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Unit Weight	2.5 lb
Relevant Standards	OSHA 1926.502 and 1910.66

Distributed by Fall Protection Distributors, LLC, an authorized FallTech dealer. standingseamroofanchor.com | 863-703-4522.

Specifications from FallTech published product data. Always follow the FallTech instruction manual.