

FallTech 82562 / C82562

82562 6' ViewPack Single-Leg Tie-Back Lanyard



Models	82562 (ANSI Z359.13-2013) · C82562 (CSA Z259.11-17)
Type	Single-leg tie-back energy-absorbing lanyard, 6 ft
Webbing	1 in jacketed dual-layer polyester, 5,000 lb minimum static strength
Energy absorber	Polyester tear-away; patented ViewPack cover w/ inspection window + WrapPack label protection
Harness end	Alloy steel snap hook
Anchorage end	Alloy steel snap hook with sliding D-ring for tie-back anchorage
Connector strength	5,000 lb min static, 3,600 lb gate
Capacity	350 lb max combined weight
Max free fall	6 ft (1.8 m)
Max absorber deployment	4.5 ft (1.4 m)
Min required fall clearance	18 ft (5.5 m) overhead, worst case
Standards	ANSI Z359.13-2013; CSA Z259.11-17; OSHA 1926.502 & 1910.66
UPC	848013065124 (82562) · 848013033765 (C82562)
Warranty	FallTech 2-year limited warranty

Distributed by Fall Protection Distributors, LLC • Call 863-703-4522 • Specs from FallTech manuals MSAL01ALX (ANSI) and CMSAL01 (CSA); subject to change without notice.