

FallTech ViewPack Tie-Back Lanyard, 6 ft Single

Part Number(s): 825623A | Brand: FallTech | Product Specification Sheet

Features

- Constructed with jacketed double-layer polyester webbing for added strength and abrasion resistance
- Features Tie-back D-ring for wrap-around anchoring and eliminates the need for a separate tie-off anchor point.
- Energy absorber features patented ViewPack cover with inspection window
- ViewPack cover also features WrapPack label protection
- Includes aluminum alloy snap hooks for harness attachment and D-ring anchorage connection
- Complies with ANSI Z359.13-2013



Specifications

Description	Aluminum Rebar Hook
Static Strength	5,000 lb min.
ANSI Lanyard Class	6' free fall
Max. Arrest Distance	48"
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
Webbing	Polyester; 5,000 lb min. static strength
Energy Absorber	Polyester tear-away
Connectors	Aluminum alloy; 5,000 lb min. static strength with 3,600 lb gate strength
D-ring	Plated alloy steel; 5,000 lb min. static strength
Unit Weight	3.44 lb
Relevant Standards	ANSI Z359.13-2013; OSHA 1926.502 and 1910.66

Distributed by Fall Protection Distributors, LLC, an authorized FallTech dealer. standingseamroofanchor.com | 863-703-4522.

Specifications from FallTech published product data. Always follow the FallTech instruction manual.