

FallTech FR84106TP3S 6 ft FT-X EdgeCore LE SRL-P, Twin-Leg

FallTech | Fall Protection Distributors, LLC

Type	6' FT-X EdgeCore Class 2 leading edge personal SRL-P, twin-leg, field replaceable
Standard	ANSI Z359.14-2021 Class 2 SRL-P; CSA Z259.2.2-2017
Lifeline	EdgeCore Kevlar cable core with UV-resistant composite jacket; 5,000 lb min.
Connectors	Steel swivel rebar hooks; 5,000 lb min. with 3,600 lb gate strength
Dorsal connector	Aluminum alloy; 3,600 lb min.
Field replaceability	SpeedLink field-replaceable retractable legs; replacement leg part FR84106RP3S
Energy absorber	Polyester tear-away with fall clearance charts inside cover
Static strength	3,600 lb min.
Average arrest force	1,350 lb max.
Maximum arrest force	1,800 lb
Maximum arrest distance	42 in.
Capacity	130 to 310 lb ANSI; 130 to 420 lb OSHA
Edge rating	Leading edge; below D-ring tie-off up to 5 ft per manual
Standards	ANSI Z359.14-2021; CSA Z259.2.2-2017; OSHA 1926.502 and 1910.66
Warranty	FallTech 2-year limited warranty against defects in materials and workmanship