

727620LE

Contractor Leading Edge Class 2 SRL with 20' Galvanized Steel Cable and Anchorage Carabiner

Features :

- 7/32" galvanized steel cable lifeline with load-indicating swivel snap hook
- Internal inertial braking system provides positive stopping action and uniform deceleration.
- Integrated external ViewPack® energy absorber strengthens the braking system and preserves lifeline integrity
- Durable glass-filled nylon housing extends service life
- Integrated lifeline hand-grip simplifies dorsal connection and recoil spring helps prevent lifeline lock-up
- Load-indicating snap hook provides visual fall event indication
- Complies with ANSI Z359.14-2021 Class 2 SRL. [Learn more and download White Paper](#)



Material Specifications	
Cable	7/32" galvanized steel; 3,600 lb min. static strength
Energy Absorber	Polyester tear-away
Lifeline Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Anchorage Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
Static Strength	3,600 lb min.
ANSI SRL Class/Type	Class 2 SRL
Avg. Arrest Force	1,350 lb
Max. Arrest Force	1,800 lb
Max. Arrest Distance	42"
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 310 lb max.

Compliant With:	
OSHA	1926.502 and 1910.66
ANSI	Z359.14-2021

Sizes & Part Numbers				
727620LE - 20' (ANSI Compliant)	727630LE - 30' (ANSI Compliant)	C727630LE - 30' (CSA Compliant)	727650LE - 50' (ANSI Compliant)	C727650LE - 50' (CSA Compliant)