

C83709SB7

9' DuraTech® Cable SRL with Steel Swivel Snap Hook, Includes Steel Anchorage Carabiner - CSA

Features :

- Compact size is simple to install and relocate as worksite changes require
- 3/16" galvanized steel cable lifeline with load-indicating swivel snap hook.
- Glass-filled nylon housing contributes unmatched impact resistance
- Integrated aluminum alloy swivel-eye helps to prevent lifeline twisting for smooth operation
- Includes alloy steel anchorage carabiner
- Complies with CSA Z259.2.2-17



Material Specifications	
Cable	3/16" galvanized steel; 3,400 lb min. static strength
Lifeline Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Anchorage Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
Static Strength	3,600 lb min.
ANSI SRL Class/Type	Class 1 SRL-P
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
Max. Arrest Distance	42"
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 310 lb max.

Compliant With:	
OSHA	1926.502 and 1910.66
ANSI	Z359.14-2014
CSA	Z259.2.2-2017

Sizes & Part Numbers		
83709SB7 (ANSI Compliant)	C83709SB7 (CSA Compliant)	