



# SPEC SHEET

## TAN10 MEGApod 10' Aluminum Tripod

### Design Specifications

Adjustable Height: 71.65" (1.82 m) - 92.91" (2.36 m)

Distance Between Legs:

At minimum tripod height: 58.26" (1.48 m)  
At maximum tripod height: 98.42" (2.5 m)

Height adjustment achieved by sliding telescopic legs

Includes two eyebolts for personal protective equipment attachment

Two pulley system provided to pass the wire rope of winch mounted on one leg and retrieval block on the other leg simultaneously



Includes mounting brackets for winch and retrieval system installation

### Material Specifications

Tripod Material	Prime Quality Aluminum Alloy
Tripod Legs Finish	Anodized
Tripod Head Finish	Powder Coated
Locking Pins Finish	Polished
Locking Pins Material	Stainless Steel
Load Capacity	310 lbs.
Weight	52.5 lbs.

### Relevant Standards

OSHA	1926
	1910
ANSI	Z359.1-2007
EN	795:2012 Type B



#### WARNINGS:

- Do not skip user instructions supplied with this product.
- Alteration or misuse of this product or failure to follow instructions may lead to serious injury or even death.



info@frontlinefall.com

www.frontlinefall.com



# SPEC SHEET

## RUW60 MEGApod 60' Confined Space Winch with Galvanized Steel Cable

### Design Specifications

Includes mounting plate having two pin locking bolts for mounting to MEGApod tripod leg

Comes with rugged and long-lasting galvanized steel wire rope of 15/64" diameter

Includes swiveling steel snaphook as a connector for better mobility and user harness connection

### Material Specifications

Cable	Galvanized steel wire
Cable Length	60 ft. (18.28m)
Cable Diameter	15/64"
Body Material	Galvanized Steel
Rated Load Capacity	310 lbs.
Weight	39 lbs.

### Relevant Standards

ANSI	Z359.4-2013
OSHA	CFR 1926
	CFR 1910



#### WARNINGS:

- Do not skip user instructions supplied with this product.
- Alteration or misuse of this product or failure to follow instructions may lead to serious injury or even death.



info@frontlinefall.com

www.frontlinefall.com



# SPEC SHEET

## RPG603W 60' 3-Way Self Retractable Lifeline with Retrieval System

### Design Specifications

Retrieval fall arrester block in polymer casing coupled with hoisting winch to enable easy retrieval of victim

The locking pin on the side of the casing at the base of the handle allows this dual system to work in independent fall arrest & winch mode

Can be easily mounted on the leg of the MEGApod system with specialized bracket (TACBU)

### Physical Parameters

Has swivel anchorage eye at anchorage end

Swivel steel snap hook with load Indicator at attachment end

Robust & durable plastic casing

### Material Specifications

Cable Galvanized steel wire rope

Cable Length 60 ft. (18.28m)

Cable Diameter 3/16"

Min. Breaking Strength 3,400 lbs


Weight 20.3 lbs

### Relevant Standards

ANSI Z359.14-2014

OSHA CFR 1926

CFR 1910



#### WARNINGS:

- Do not skip user instructions supplied with this product.
- Alteration or misuse of this product or failure to follow instructions may lead to serious injury or even death.



info@frontlinefall.com

www.frontlinefall.com