



1000 Cranberry Woods Drive,
Cranberry Township, PA 16066

MSA Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014
IAC-23-062 - Z04 Rev 1

Statement of Conformity: MSA declares that the
Dyna-Glide System with Skylotec Fall Arrester
is in conformity with the requirements of
OSHA 1910.29-2019 & 1910.140-2019
OSHA 1926.502-1995 & 1926.1053-2014
ANSI A14.3-2008

Product Code	Model / Part Numbers Covered
IAC-23-062	Dyna-Glide Systems are Engineered Fall Protection Systems, therefore there is no standard salable part number.

ANSI/ISEA 125-2014 conformity assessment method: ☒ Level 1 ☐ Level 2

For Level 2, information about ISO 17025-accredited facility in which the product was tested:

☒ The test facility is an independent 3rd Party ISO 17025-accredited facility
ISO Accrediting Agency: UKAS 0248

☒ The test facility is owned or partially owned by an entity within supplier's corporate structure, or within the manufacturing stream for this product, including subcontractors and sub-suppliers.

ISO Accrediting Agency: ANAB ANSI National Accreditation Board

Report	Test Facility Used:	Test Facility Document #
1	Skylotec	20160705 Skylotec compatibility MSA
2	MSA FPLab	Dynaglide-Skylotec Test Plan

For additional information about this product(s), please contact MSA Customer Service at 1-800-MSA-2222. When requesting information, please reference model number(s).

Brooke Conroy
Brooke Conroy (Aug 4, 2022 11:34 EDT)

QA Rep: Brooke Conroy

Aug 4, 2022

Date: MM/DD/YYYY

Timothy J. Botti
Timothy J. Botti (Aug 7, 2022 14:04 EDT)

Qualified Person: Tim Botti

Aug 7, 2022

Date: MM/DD/YYYY

Performance Details

Revision 1

Report	Standard and Product Requirements	Acceptance Criteria	Pass / Fail
1	ANSI Z359.16 Section 3.1.3.2 & 4.2.1 (Dynamic Drop)	Favg < 1350 lbf, Fmax < 1800 lbf, Total Fall Distance < 39"	Pass
1	ANSI Z359.16 Section 3.1.4.2 & 4.2.2.3 (Proof Load)	Energy Absorber Extension < .8"	Pass
1	ANSI Z359.16 Section 3.1.4.3 & 4.2.2.4 (Static Test)	Fmax > 3600 lbf	Pass
1	ANSI Z359.16 Section 3.1.4.4 & 4.2.2.5 (Energy Absorber Static Test)	Fmax > 5000 lbf	Pass
1	ANSI Z359.16 Section 3.2.5.1 (Locking on the Carrier)	Pass	Pass
1	ANSI Z359.16 Section 3.2.5.2 & 4.2.3 (Fall Back)	Maximum Carrier Movement < 20", Total Fall Distance < 39"	Pass
1	ANSI Z359.16 Section 3.2.5.3 & 4.2.4 (Locking Function Test)	Maximum Carrier Movement < 20", Total Fall Distance < 39"	Pass
2	CSA Z259.2.4-12 Section 5.3.3 (Fall Back Test)	Maximum Carrier Movement < 20", Total Fall Distance < 39"	Pass
2	CSA Z259.2.4-12 Section 5.3.6 (Dynamic Strength)	Maximum Carrier Movement < 12"	Pass
2	OSHA 1910.66 Appendix C Section I(d)(2)(ii) & II(d) (Heavy Worker Force)	Fmax < 2520 lbf	Pass
2	OSHA 1910.66 Appendix C Section I(d)(2)(ii) & II(c) (Heavy Worker Strength)	Arrest and suspend the test weight	Pass
2	ANSI A14.3 Section 7.5.4 (Dynamic Performance)	Maximum Carrier Movement < 6"	Pass
2	ANSI A14.3 Section 7.5.2 (Dynamic Strength)	Arrest and suspend the test weight	Pass
2	ANSI A14.3 Section 7.5.3 (Static Strength)	Fmax > 1000 lbf	Pass