

# V-SERIES® Fall Protection

V-FORM+ Harness  
& V-EDGE® Personal Fall Limiters



To support you in your conversations with customers around Fall Protection needs, samples of the V-FORM+ Harness and V-EDGE Personal Fall Limiter are being provided.

**Target Markets for both of these products include:**

- Construction — Heavy and Commercial
- General Industry
- OGP

The following bulletin provides differentiating benefits of these products along with associated part numbers that are stocked by MSA.

If you have additional questions, please reach out to your local MSA sales manager, or contact our Customer Service department at [us.cs@msasafety.com](mailto:us.cs@msasafety.com).

WE KNOW WHAT'S AT STAKE.

## V-FORM+ Harness




### Superior Comfort




The patent-pending racing-style buckle allows for a close, comfortable harness fit—eliminating the need for bulky chest straps or cumbersome buckles.

### Increased Flexibility



The racing-style buckle creates an athletic cut, contouring the harness to the body and improving upper torso movement on the job.

### Adjustability



Dedicated attachment point for Personal Fall Limiters allows for quick and easy attachment, and keeps your back D-ring free for other use.

### Markets

- Construction
- General Industry
- Oil and Gas

### Applications

- Working at Height
- Confined Space

### Harness Size Chart

|                                                                                     | ft.    | (m)   |      |      |      |      |      |       |       |       |       |       |       |       |
|-------------------------------------------------------------------------------------|--------|-------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
|  | 6'-6"  | (2.0) |      |      |      |      |      |       |       |       |       |       |       |       |
|                                                                                     | 6'-4"  | (1.9) |      |      |      |      |      |       |       |       |       |       |       |       |
|                                                                                     | 6'-2"  | (1.9) |      |      |      |      |      |       |       |       |       |       |       |       |
|                                                                                     | 6'-0"  | (1.8) |      |      |      |      |      |       |       |       |       |       |       |       |
|                                                                                     | 5'-10" | (1.8) |      |      |      |      |      |       |       |       |       |       |       |       |
|                                                                                     | 5'-8"  | (1.7) |      |      |      |      |      |       |       |       |       |       |       |       |
|                                                                                     | 5'-6"  | (1.7) |      |      |      |      |      |       |       |       |       |       |       |       |
|                                                                                     | 5'-4"  | (1.6) |      |      |      |      |      |       |       |       |       |       |       |       |
|                                                                                     | 5'-2"  | (1.6) |      |      |      |      |      |       |       |       |       |       |       |       |
|                                                                                     | 5'-0"  | (1.5) |      |      |      |      |      |       |       |       |       |       |       |       |
|  | lb.    |       |      |      |      |      |      |       |       |       |       |       |       |       |
|                                                                                     | (kg)   | 110   | 130  | 150  | 170  | 190  | 210  | 230   | 250   | 270   | 290   | 310   | 330   | 400   |
|                                                                                     |        | (50)  | (59) | (68) | (77) | (86) | (95) | (105) | (114) | (123) | (132) | (141) | (150) | (181) |
|                                                                                     |        |       |      |      |      |      |      |       |       |       |       |       |       |       |
|                                                                                     |        |       |      |      |      |      |      |       |       |       |       |       |       |       |
|                                                                                     |        |       |      |      |      |      |      |       |       |       |       |       |       |       |
|                                                                                     |        |       |      |      |      |      |      |       |       |       |       |       |       |       |
|                                                                                     |        |       |      |      |      |      |      |       |       |       |       |       |       |       |
|                                                                                     |        |       |      |      |      |      |      |       |       |       |       |       |       |       |
|                                                                                     |        |       |      |      |      |      |      |       |       |       |       |       |       |       |

# V-EDGE 8 ft. (2.4 m) Personal Fall Limiters




## Simplified Selection



The V-EDGE PFL can be used in a variety of applications where sharp edge hazards are a concern, making product selection simple.

## Easy to Connect



Get to work faster. Save time and frustration with a sleek and simple locking pin attachment.

## Lower Cost of Ownership



With a stainless steel housing and protective cover for the energy absorber, the V-EDGE PFL is built to fight the toughest elements, saving you time and money on product replacements.

## Markets

- Construction
- General Industry
- Oil and Gas

## Applications

- Leading Edge Work

## V-FORM+ Standard Harness

| Part Number | D-Ring Configuration |            |             | Size |     |     |     | Leg Buckle Type | Padding  | Standards                             |
|-------------|----------------------|------------|-------------|------|-----|-----|-----|-----------------|----------|---------------------------------------|
|             | Back                 | Back, Hips | Back, Chest | XSM  | STD | XLG | SXL | Tongue Buckle   | Shoulder | ANSI Z359.11/<br>CSA Z259.10/<br>OSHA |
| 10206085    | ■                    |            |             | ■    |     |     |     | ■               | ■        | ■                                     |
| 10205845    | ■                    |            |             |      | ■   |     |     | ■               | ■        | ■                                     |
| 10206086    | ■                    |            |             |      |     | ■   |     | ■               | ■        | ■                                     |
| 10206087    | ■                    |            |             |      |     |     | ■   | ■               | ■        | ■                                     |
| 10206088    |                      | ■          |             | ■    |     |     |     | ■               | ■        | ■                                     |
| 10206089    |                      | ■          |             |      | ■   |     |     | ■               | ■        | ■                                     |
| 10206090    |                      | ■          |             |      |     | ■   |     | ■               | ■        | ■                                     |
| 10206091    |                      | ■          |             |      |     |     | ■   | ■               | ■        | ■                                     |
| 10206092    |                      |            | ■           | ■    |     |     |     | ■               | ■        | ■                                     |
| 10206093    |                      |            | ■           |      | ■   |     |     | ■               | ■        | ■                                     |
| 10206094    |                      |            | ■           |      |     | ■   |     | ■               | ■        | ■                                     |
| 10206095    |                      |            | ■           |      |     |     | ■   | ■               | ■        | ■                                     |



P/N 10206093



P/N 10206161

## V-FORM+ Construction Harness

| Part Number | D-Ring Configuration |            |             | Size |     |     |     | Leg Buckle Type | Padding  | Standards                             |
|-------------|----------------------|------------|-------------|------|-----|-----|-----|-----------------|----------|---------------------------------------|
|             | Back                 | Back, Hips | Back, Chest | XSM  | STD | XLG | SXL | Tongue Buckle   | Shoulder | ANSI Z359.11/<br>CSA Z259.10/<br>OSHA |
| 10206160    |                      | ■          |             | ■    |     |     |     | ■               |          | ■                                     |
| 10206161    |                      | ■          |             |      | ■   |     |     | ■               |          | ■                                     |
| 10206162    |                      | ■          |             |      |     | ■   |     | ■               |          | ■                                     |
| 10206163    |                      | ■          |             |      |     |     | ■   | ■               |          | ■                                     |

## V-EDGE Personal Fall Limiter

| Part Number | Type       |          | Line Length   | Line Type | Anchorage Connection | Harness Connection | Standards |      |     |
|-------------|------------|----------|---------------|-----------|----------------------|--------------------|-----------|------|-----|
|             | Single-Leg | Twin-Leg |               |           |                      |                    | ANSI      | OSHA | CSA |
| 63062-00A   | ■          |          | 8 ft. (2.4 m) | Cable     | AL36CL Snaphook      | Locking Pin        | ■         | ■    |     |
| 63062-00E   | ■          |          | 8 ft. (2.4 m) | Cable     | 36CS Snaphook        | Locking Pin        | ■         | ■    |     |
| 63062-00ACA | ■          |          | 8 ft. (2.4 m) | Cable     | AL36CL Snaphook      | Locking Pin        |           |      | ■   |
| 63062-00ECA | ■          |          | 8 ft. (2.4 m) | Cable     | Swivel Snaphook      | Locking Pin        |           |      | ■   |
| 63162-00A   |            | ■        | 8 ft. (2.4 m) | Cable     | AL36CL Snaphook (2)  | Locking Pin        | ■         | ■    |     |
| 63162-00E   |            | ■        | 8 ft. (2.4 m) | Cable     | 36CS Snaphook (2)    | Locking Pin        | ■         | ■    |     |
| 63162-00F   |            | ■        | 8 ft. (2.4 m) | Cable     | 36CL Snaphook (2)    | Locking Pin        | ■         | ■    |     |
| 63162-00ACA |            | ■        | 8 ft. (2.4 m) | Cable     | AL36CL Snaphook (2)  | Locking Pin        |           |      | ■   |
| 63162-00ECA |            | ■        | 8 ft. (2.4 m) | Cable     | Swivel Snaphook (2)  | Locking Pin        |           |      | ■   |
| 63162-00FCA |            | ■        | 8 ft. (2.4 m) | Cable     | 36CL Snaphook (2)    | Locking Pin        |           |      | ■   |



P/N 63062-00A (left)  
P/N 63162-00A (right)

Note: This Bulletin contains only a general description of the products shown. While product uses and performance capabilities are generally described, the products shall not, under any circumstances, be used by untrained or unqualified individuals. The products shall not be used until the product instructions/user manual, which contains detailed information concerning the proper use and care of the products, including any warnings or cautions, have been thoroughly read and understood. Specifications are subject to change without prior notice. MSA is a registered trademark of MSA Technology, LLC in the US, Europe, and other Countries. For all other trademarks visit <https://us.msasafety.com/Trademarks>.

MSA operates in over 40 countries worldwide. To find an MSA office near you, please visit [MSAsafety.com/offices](https://us.msasafety.com/offices).