

MSA Competent Person Inspection Log: V-SERIES® Restraint Lanyard Webbing



Competent Inspector Name	Inspection Date
Part No.	Length
Date Made	Serial No.
User Name	ID/Job Title

COMPONENT	QTY/UNIT	OVERALL ASSESSMENT	COMMENTS
Labels			
Label Packet			
Hardware			
Snaphook			
Adjuster			
Webbing			
Lifeline			
Stitching			
Box Stitches			



SERVICES & SOLUTIONS

Need training? MSAsafety.com/training



Scan for V-SERIES Restraint Lanyard Literature and Instruction Manual

DISPOSITION (Check one)

PASS
Remain in service

FAIL
Mark unusable and dispose

CORRECTIVE ACTION
Repair or clean

CORRECTIVE ACTION DESCRIPTION

CORRECTIVE ACTION DATE

OVERALL ASSESSMENT		
If components exhibit any of the conditions listed below, mark the corresponding item as failure and/or corrective action if applicable		
Labels	Webbing	Stitching
Missing	Abrasion	Broken
Not Legible	Burn	Loose Threads
Hardware	Chemical/UV	Missing
Burr	Cut	
Change of Color	Fray	
Change of Shape	Melt	
Cracks	Missing	
Dents	Non-Approved Marker	
Excessive Wear	Separated	
Malfunction	Tape	
Missing	Tear	
Unauthorized Modification		

MSA Inspection Recommendations

This inspection log can be used as a guide for pre-use User inspections but is not a replacement for the Instruction Manual. For additional warnings and product details, reference the Instructional Manual. The User must inspect the restraint lanyard (RL) and check the fall arrest force indicator before each use. All RLs must be formally inspected by a competent person prior to first use. MSA requires that all RLs be inspected by a competent person other than the user at intervals of no more than one year per applicable standard or as specified by a formal fall protection program. The interval will be dictated by the usage, local regulations, and environmental conditions, and will be at least annually. Record formal inspections in the Inspection Log. Indelibly mark the inspection grid attached to the RL. Do not use a RL with a formal inspection date older than one (1) year unless under provision of formal inspection program.