

## SINGLE USE ROOF ANCHOR

The Malta Dynamics Single-Use Roof Anchor is a must-have for any roofer's safety kit. Designed to bend easily over the roof peak or adjust to match varying roof pitches, this disposable anchor provides a secure tie-off point without causing permanent damage to the structure. Its versatile shape and reliable performance make it ideal for new construction, remodeling, or reroofing projects.

Built from durable, zinc-plated alloy steel, this anchor is both lightweight and strong. It installs quickly using the included eight (8) 16d common nails, making setup fast and hassle-free. With a user weight capacity of 130–310 lbs., this anchor has a minimum breaking strength of 5,000 lbs. and is tested to meet OSHA 1926.502, OSHA 1910.66, and ANSI Z359.18-2017 standards.

To ensure maximum safety, always mount the anchor into a solid structural member such as a roof truss or rafter. A fall protection system is only as strong as its anchor point.

Whether you're tackling a residential remodel or a commercial reroof, this single-use roof anchor helps you get the job done efficiently and safely.

### KEY FEATURES

#### 1. Pre-punched attachment holes for nails (x8)

- Flexible design conforms to roof peaks or lays flat to match roof pitch
- Lightweight and easy to install with included (8) 16d common nails
- Removable design leaves no permanent damage to the roof
- Constructed from zinc-plated alloy steel for enhanced durability and corrosion resistance
- Minimum breaking strength: 5,000 lbs.
- Supports user weights from 130 to 310 lbs.
- Complies with OSHA 1926.502, OSHA 1910.66, and ANSI Z359.18-2017



### PERFORMANCE SPECIFICATIONS

Worker Capacity Range	130-310 lbs. Max
Minimum Breaking Strength	5,000 lbs. Max

### MATERIALS SPECIFICATIONS

Anchor	Zinc Plate Alloy Steel
Nails	16d common nails (included)

### FALL PROTECTION STANDARDS

OSHA	1926.502, 1910.66
ANSI	Z359.18-2017 Type A

PART #	PACK	WEIGHT
A6318	1	1.3 lbs.
A6318-2	2	2.6 lbs.
A6318-8	8	10.4 lbs.
A6318-25	25	32.5 lbs.