

MESH FACE SHIELD INSTRUCTIONS FOR USE

INTRODUCTION

This helmet mounted mesh face shield has been designed to provide protection to meet or exceed ANSI/ISEA Z87.1 and EN 1731-S. They offer protection to the wearer against flying debris without the risk of lens fogging.

READ ALL INSTRUCTIONS AND WARNINGS BEFORE USING FACE SHIELD

INSTALLATION AND REMOVAL

With the face shield facing the forward direction, insert tabs into side slots of the helmet. Push until the tabs are locked into place.

To remove, push tabs outward from inside of the helmet then push the tabs out of the helmet.

COMPATIBILITY

Compatible for use with Malta Dynamic Apex Safety Helmets and Helmet Mounted Ear Muffs

INSPECTION AND CLEANING

NEVER ALTER OR MODIFY THE FACE SHIELD. ALWAYS USE OUR REPLACEMENT PARTS.

Inspect your face shield before every use. Check for cracks, distortion, and damage to mesh. Replace immediately if any signs of wear, damage, abuse, or environmental degradation is found. If mesh shield is subjected to a forcible impact, discard immediately.

Clean all components regularly with a mild detergent or disinfectant in lukewarm water. Do not use paints, solvents, chemicals, adhesives, gasoline or like substances on this helmet. Such substances may destroy the impact resistance and other protective properties of the face shield without being apparent or readily detectable by the user.

STORAGE

Store in a ventilated place without direct sunlight and contact with any solvent.

WARNING

Failure to follow these warnings can result in altered face shield performances and may result in serious personal injury or death

Face shields offer secondary protection and must be worn with spectacles or goggles.

Never alter or modify this face shield in any way.

Never use paint, solvents, or hydrocarbon type cleaners (that is, thinner, gasoline, kerosene etc.) on the face shield. These may cause unnoticeable damage.



800-494-1840
MaltaDynamics.com
210 13th Street
Malta, OH 43758 USA