



CLASS 2-P EDGEHOG LEADING EDGE SRLS

The Malta Dynamics' Leading Edge SRLs provide you and your workers with foot level tie-off and sharp edge applications. This compact and lightweight Class 2-P Leading Edge SRL offers a quick-action braking system, swivel top and slide life-line exit with a rubber ergonomic handle. The ANSI Class 2-P rating features a versatile design, allowing for use above and below the back D-Ring. With a maximum arresting force of 1,600 lbs., this high-quality equipment is a must-have for your work site. It comes equipped with a built-in back pad to make wearing the SRLs on your back much more comfortable.



KEY FEATURES

1. Galvanized Steel LE Approved Cable
2. Backpack Style Energy Absorber
3. Durable Housing
4. Rubber Ergonomic Handle
5. 360° Swivel Connector (on snap hooks)

- Provides maximum comfort and safety
- Comes standard: full shoulder, back, waist and leg comfort padding
- Built-in lanyard keepers on both sides
- Premium aglets on all adjustment straps
- Impact indicator
- Deluxe label protector

PERFORMANCE SPECIFICATIONS

| | |
|-----------------------|--------------|
| Worker Capacity Range | 130-310 lbs. |
|-----------------------|--------------|

OVERHEAD APPLICATIONS

| | |
|-------------------------|-----------|
| Max Arresting Force | 1,600 lbf |
| Average Arresting Force | 1,100 lbf |
| Max Arresting Distance | 42" |

LEADING EDGE APPLICATIONS

| | |
|---|-------|
| Max Free Fall Distance | 6' |
| Minimum Setback Distance | 48" |
| Clearance Required When Falling Over Edge | 13.5' |

MATERIALS SPECIFICATIONS

| | |
|-----------------------------------|------------------------|
| D-Rings/Buckles/Adjustments/Cable | Galvanized/Alloy Steel |
| Housing | Thermoplastic Polymer |

FALL PROTECTION STANDARDS

| | |
|------|---|
| ANSI | ANSI Z359.14-2021 Class 2-P, ANSI A10.32-12 |
| OSHA | 1926 Subpart M, 1910.66, 1926.502 |

| PART # | SIZE | WEIGHT |
|---------|-----------------------|-----------|
| LE3261 | 6' w/Snap Hook | 4.21 lbs. |
| LE3261D | 6' Dual w/Snap Hook | 7.47 lbs. |
| LE3263 | 6' w/Rebar Hook | 4.21 lbs. |
| LE3263D | 6' Dual w/Rebar Hook | 7.47 lbs. |
| LE3311 | 10' w/Snap Hook | 4.21 lbs. |
| LE3311D | 10' Dual w/Snap Hook | 7.47 lbs. |
| LE3313 | 10' w/Rebar Hook | 4.21 lbs. |
| LE3313D | 10' Dual w/Rebar Hook | 7.47 lbs. |