



## CLASS 2 EDGEHOG LEADING EDGE SRLS

The Class 2 Edgehog Leading Edge SRLs with snap hook features a 360° swivel top connection point that allows the durable thermoplastic housing to rotate as you move and boasts a sturdy galvanized steel cable with built-in strike test grip. These SRLs extends as the user moves away from the anchor point and retracts as the user moves back toward the anchorage point. The ANSI Class 2 rating features a versatile design, allowing for use above and below the back D-Ring. The Malta Dynamics Leading Edge Self-Retracting Lifeline with Snap Hook is tested to meet the strict standards of ANSI Z359.14-2021 Class 2, ANSI A10.32-12, OSHA 1926 Subpart M and OSHA 1910.



### KEY FEATURES

1. 360 Swivel Top Connection Point
2. Built-In-Easy-Carry Handle
3. Galvanized Steel Cable
4. Built-in Strike Test Grip
5. Integral Shock Energy Absorption System
6. Self-locking Alloy Steel Snap Hook

- Lightweight and Compact Design
- Durable Thermoplastic Housing
- Quick- Action Braking System

### PERFORMANCE SPECIFICATIONS

Worker Capacity Range	130-310 lbs.
-----------------------	--------------

#### OVERHEAD APPLICATIONS

Max Arresting Force	1,600 lbf
Average Arresting Force	1,100 lbf
Max Arresting Distance	42"

#### LEADING EDGE APPLICATIONS

Max Free Fall Distance	6'
Minimum Setback Distance	24"
Clearance Required When Falling Over Edge	18.5'

### MATERIALS SPECIFICATIONS

Cable	Galvanized Steel
Housing	Thermoplastic Polymer
Snap Hook	Alloy Steel

### FALL PROTECTION STANDARDS

ANSI	ANSI Z359.14-2021 Class 2, ANSI A10.32-12
OSHA	1926 Subpart M and OSHA 1910

PART #	SIZE	WEIGHT
LE7020-G2	20ft	9.3 lbs.
LE7030-G2	30ft	9.9 lbs.
LE7050-G2	50ft	15.61 lbs.