



### Technical Data

|                                |                   |
|--------------------------------|-------------------|
| Color                          | Silver            |
| Sizes Available                | OS                |
| Packaging                      | Boxed             |
| Packed                         | 20/Case           |
| Case Weight (lbs)              | 0.00              |
| Country of Origin              | United States     |
| Anchor Type                    | Concrete Anchor   |
| Connector Type                 | Steel             |
| Certifications                 | TAA Compliant     |
| Anchorage Connectors Rated For | 22 kN (5,000 lbs) |

### Miller®

#### Permanent D-Bolt Anchor

- Made from drop-forged alloy steel for enhanced durability, to withstand harsh conditions
- Single D-ring design configuration for secure attachment to a single anchorage point
- Permanent installation, suitable for concrete applications
- Designed for up to 4-inch (102 mm) working thickness
- Tensile strength rated for up to 5,000 lbs.
- Supports up to 400 lbs, accommodating a wide range of workers and equipment
- Meets ANSI A10.32, ANSI Z359.1-2007, OSHA 1910.66, and OSHA 1926.502(d) standards

## SKU Information

| SKU  | COLOR  | SIZE | UPC          | UPC (INNER) | UPC (CASE) |
|------|--------|------|--------------|-------------|------------|
| 417/ | Silver | OS   | 612230054328 |             |            |