

RS-20 Dual Hole Anchors

RS-20 Anchors

RS-20 Anchors are specified for permanent installation onto wood framing with nails or screws. Ideal for concrete or clay tile roofing. Ridge installation requires 1 anchor for each side.

Features

- Fall arrest and fall restraint
- Dual hole models specified for nails, HeadLock, WS, Blazer and Bugle Head screws
- 5,000lb min. tensile strength
- 8pc sst spiral shank nails
- 2pc butyl flashing strips
- Instruction manual

Fastener Pack

8pc SST Nails



2pc Butyl Strips



Compliance

ANSI Z359.18 Type A
OSHA 1926.502

Dual Hole Model Fastener Options*

- Bugle Head sst screws
- HeadLok flat head screws
- Blazer metal deck screws
- WS wood screws

* Consult SAS catalog for fastener specifications

RS-20 Ordering Information

Part No.	△ Package	No.Pcs	Wt	D-ring	Material Type	Fastener Types
2816-D	Retail	1	1lb	Forged	17ga Dacromet Coated Steel	Nails and Screws Consult Instruction Manual
2816-BD	Bulk*	20	21lb			
2816-DS	Retail	1	1lb	Forged or Stamped	20ga 430sst	
2816-BDS	Bulk*	20	21lb			

△ Specify at time of ordering


*Min. Order 20pcs

Bulk Box Contents

- 20 Anchors
- 20ea 8pc fastener packs
- 20ea 2pc butyl strip packs
- 20ea manuals



No.2816-D/2816-DS Dual Fastener Holes



No.2816-D

Forged D-ring

Length 17-1/2"



No.2816-DS



Retail Packages No.2816-D No.2816-DS



Super Anchor Safety

17731 147th Street SE
Monroe, WA 98272, USA
www.superanchor.com
1-855-301-4575