

SUPER ANCHOR SAFETY®

FALL PROTECTION EQUIPMENT

The Best in Fall Arrest



Super Anchor Safety – Warranty & Statement of Compliance

Warranty:

Super Anchor Safety (SAS) warrants to the purchaser that all products are free from defect in material and workmanship at the time of shipment. This warranty is limited to product replacement for a period of one (1) year from the date of installation or use by the owner, provided that this period shall not exceed two (2) years from the date of shipment. This warranty only covers defects in material and workmanship. It does not cover conditions resulting from normal wear, neglect, abuse or accident. This product warranty does not cover oxidation of zinc, dacromet or powder coatings used on permanent and temporary anchors that results from connector abrasion unless the coating can be shown to be defective at the time of purchase. This warranty is non-transferable. Any unused defective product will be replaced at no charge by returning the product to Super Anchor Safety or to the Distributor the product was purchased from.

Permanent Anchor Warranty:

Super Anchor Safety warrants to the purchaser that all anchors sold as a permanent fixture with Hot Dip Galvanizing, Stainless Steel and Thermo-Plastic finishes are fully warranted against failure due to defects in materials or workmanship for a period of five (5) years from the date of initial installation. SAS does not warranty the installation or flashing system used to waterproof the anchors. The SAS factory warranty is void if the product has been modified or has not been used in accordance with SAS specifications and instructions for that product. Anchors that have been removed from service due to re-roofing or remodel of the structure they were originally attached to, must be inspected by SAS factory representative or a competent person before being reinstalled.

Statement of Compliance:

Super Anchor Safety products comply with industrial safety standards as specified on the label at the time of shipment. Copies of the Instruction/Specification Manuals and Product Label are available at www.superanchor.com or by calling toll-free 855-301-4575

