



CR3-EDGE

10ft Self-Retracting Lifeline

The new CR3-Edge 10 ft self-retracting lifeline can be used for numerous applications across the job site where the connecting device has the potential to impact the edge of the hazard in the event of a fall. This robust Class 2 SRL offers a durable and compact design to keep workers safe in the most extreme conditions.

Class
2

Anchor above
or below
dorsal D-ring

**HEIGHT SAFETY.
SIMPLIFIED.**

guardianfall.com



CR3-EDGE

10 ft Self-Retracting Lifeline

Class

2

Anchor above
or below
dorsal D-ring



Hook Options



Steel swivel snap hook



Key features & benefits

Swivel top connection point

Swivels 360 degrees to ensure the device remains in the best orientation during use and also helps prevent lifeline snagging or tangling. Double locking carabiner included.

Thermoplastic housing

Super lightweight & durable for long lasting use in the toughest applications

QR code enabled labels

Easy access to product information

Rubber lifeline stopper

Doubles as a convenient hand-grip

Steel cable lifeline

Resists cuts and abrasions

Guardian shock pack cover

Helps increase product longevity and protect safety labeling

Integrated fall clearance charts

Fall clearance charts integrated into shock pack cover for easy access to clearance charts anytime, anywhere

Swivel snap hook

Swivels 360 degrees to ensure the device remains in the best orientation

Specifications

User weight range (including clothing, tools, & equipment)

ANSI (LE use) | 130-310 lb

OSHA (Non-LE use) | 100-420 lb

OSHA (LE USE) | 100-310 lb

Max. Arrest Force | 1,350 lb

Avg. Arrest Force | 1,150 lb

Materials | Galvanized steel cable, aluminum, steel, polyolefin, polyester

Non-LE use (Anchor at or above dorsal D-ring)

Max. Arresting Distance | 3 ft

Max. Allowable Free Fall | Not Permitted

Min. Fall Clearance | 6 ft 6 in

LE Use (Anchor below dorsal D-ring)

Min. Setback Distance from Edge | 0 ft

Max. Arresting Distance | 8 ft 6 in

Max. Allowable Free Fall | 5 ft

Min. Fall Clearance: 17 ft

* Snap hook end must be connected to harness dorsal D-ring.

* Must not be used as personal self-retracting lifeline

Declaration of conformity

This product has been tested in an ISO 17025 accredited laboratory in accordance with all requirements specified by ANSI Z359.7.

This product conforms with the following safety regulations and consensus standard:

OSHA 1910.140 & 1926.502 | ANSI Z359.14

For more information:

+1 (800) 466 6385

info@guardianfall.com



Designed, tested,
and assembled in
the **United States**

CR3 EDGE CABLE SRL

Self-Retracting Lifeline



Class

2

Anchor above
or below
dorsal D-ring

Part number(s)	Description	Hook type	Length	OSHA User Weight Range	ANSI User Weight Range
4200007	CR3 SRL, Cable, Class 2	Steel swivel snap hook	10'	See Specifications	See Specifications

Declaration of conformity

This product has been tested in an ISO 17025 accredited laboratory in accordance with all requirements specified by ANSI Z359.7.

This product conforms with the following safety regulations and consensus standard:
OSHA 1910.140 & 1926.502 | ANSI Z359.14

For more information:

+1 (800) 466 6385

info@guardianfall.com



Designed, tested,
and assembled in
the **United States**