




CR3-EDGE CABLE SRL

Self-Retracting Lifeline

The CR3-Edge 33 ft SRL is part of Guardian's strongest SRL lineup in the industry. This Class 2 SRL is both lightweight and durable to help take on our customer's toughest tasks. This SRL includes an ergonomic carry handle for mobility on the jobsite and is designed to attach to an anchor point above or below a worker's dorsal D-ring. This device can be used for numerous applications across a jobsite where the connecting device has potential to impact the edge of a hazard in the event of a fall.



**HEIGHT SAFETY.
SIMPLIFIED.**

guardianfall.com



CR3-EDGE CABLE SRL

Self-Retracting Lifeline



Class
2

Anchor above
or below dorsal
D-ring



Key features & benefits

Swivel top connection point

Swivels 360 degrees to ensure the device remains in the best orientation during use and also helps prevent lifeline snagging or tangling. Double locking carabiner included.

Thermoplastic housing

Heavy Duty & durable for long lasting use in the toughest applications

Integrated handle

Allows for user comfort when carrying and installing the SRL

QR code enabled labels

Easy access to product information

Rubber lifeline stopper

Doubles as a convenient hand-grip

Steel cable lifeline

Resists cuts and abrasions

Guardian shock pack cover

Helps increase product longevity and protect safety labeling

Swivel snap hook

Swivels 360 degrees to ensure the device remains in the best orientation

Specifications

User weight range (including clothing, tools, & equipment)

ANSI (LE use) | 130-310 lb

OSHA (Non-LE use) | 100-420 lb

Max. Arrest Force | 1,800 lb

Avg. Arrest Force | 1,350 lb

Materials | Galvanized steel, aluminum, stainless steel, polyolefin, polyester

Non-LE use (Anchor at or above dorsal D-ring)

Max. Arresting Distance | 42 in

Max. Allowable Free Fall | Not Permitted

Min. Fall Clearance: 7 ft

LE Use (Anchor below dorsal D-ring)

Min. Setback Distance from Edge | 0 ft

Max. Arresting Distance | 8 ft 6 in

Max. Allowable Free Fall | 5 ft

Min. Fall Clearance: 17 ft



Declaration of conformity

This product has been tested in an ISO 17025 certified laboratory in accordance with all requirements specified by ANSI Z359.7.

This product conforms with the following safety regulations and consensus standard:

OSHA 1910.140 & 1926.502 | ANSI Z359.14

For more information:

+1 (800) 466 6385

info@guardianfall.com



Designed, tested
and assembled in
the **United States**

CR3-EDGE CABLE SRL
Self-Retracting Lifeline



Class

2

Anchor above
or below dorsal
D-ring

Part numbers	Description	Hook type	Length	User Weight Range
4200221	CR3 SRL, Cable, Class 2	Steel swivel snap hook	33'	See specifications

Declaration of conformity

This product has been tested in an ISO 17025 certified laboratory in accordance with all requirements specified by ANSI Z359.7.

This product conforms with the following safety regulations and consensus standard:
OSHA 1910.140 & 1926.502 | ANSI Z359.14

For more information:
+1 (800) 466 6385
info@guardianfall.com



Designed, tested
and assembled in
the **United States**