



CR5 ARC FLASH

Personal
Self-Retracting Lifeline

The CR5 9 ft Class 1 Web Arc Flash Personal SRL is part of Guardian's strongest line-up of SRLs in the industry. The 9 ft webbing and shock pack cover material is made from premium heat and burn resistant materials such as Kevlar® and Nomex® to ensure proper function and structural integrity is maintained after extreme events - such as an arc flash. This versatile Class 1 personal SRL can be used in a combination of either fall arrest or travel restraint applications.

Class

1

Anchor at or
above dorsal
D-ring

**HEIGHT SAFETY.
SIMPLIFIED.**

guardianfall.com



CR5 ARC FLASH

Personal Self-Retracting Lifeline



Class

1

Anchor at or
above dorsal
D-ring

Swivel top connection point

Thermoplastic housing

QR Code

Reinforced webbing guide

Kevlar®/Nomex® Shock Pack Cover

Steel snap hook

4200030

4200035

Key features & benefits

Swivel top connection point

Swivels 360-degrees to ensure the device remains in the best orientation during use and also helps prevent lifeline snagging or tangling

Impact modified thermoplastic housing

Super lightweight & durable for long-lasting use in the toughest applications

Digitally enabled labels

QR code for quick and easy access to up-to-date safety and product information

Kevlar®/Nomex® Shock Pack Cover

Burn and Heat resistant materials for added protection

Reinforced webbing guide

Added strength and reduces webbing friction

Multiple hook options available

Choose steel or aluminum snap or rebar hooks, depending on job requirements and anchorage type

Specifications

Class 1 SRL (ANSI Z359.14-2021)

Length | 9 ft (2,7 m)

Average Arrest Force | 1,150 lb (680 kg)

Maximum Arrest Force | 1,350 lb (612 kg)

Maximum Arrest Distance | 3 ft (100-420 lb)
,91 m (45,3-190,5 kg)

Type | SRL-P

Materials | Polyester, Impact Modified Thermoplastic resin, HMPE Webbing, Steel, Aluminum, Kevlar® and Nomex® Materials

Hook Options



Steel snap hook



Steel rebar hook



Aluminum snap hook



Aluminum rebar hook

Declaration of conformity

These products been tested in an ISO 17025 accredited laboratory in accordance with all requirements specified by ANSI/ASSP Z359.7.

This product is compliant with the following safety regulations:
ANSI Z359.14-2021 | OSHA 1910.140 & 1926.502 | ASTM F887

For more information:

+1 (800) 466 6385


customer.service@guardianfall.com



Designed and
tested in the
United States

CR5 ARC FLASH

Personal Self-Retracting Lifeline



Part number	Description	Hook type	Length	OSHA User Weight	ANSI User Weight
4200030	CR5 Class 1 Web Arc Flash SRL-P	Steel snap hook	9 ft (2,74 m)	100-420 lb (45,3 - 204 kg)	130-310 lb (58,9-140,6 kg)
4200031	CR5 Class 1 Web Arc Flash SRL-P	Aluminum snap hook	9 ft (2,74 m)	100-420 lb (45,3 - 204 kg)	130-310 lb (58,9-140,6 kg)
4200032	CR5 Class 1 Web Arc Flash SRL-P	Steel rebar hook	9 ft (2,74 m)	100-420 lb (45,3 - 204 kg)	130-310 lb (58,9-140,6 kg)
4200033	CR5 Class 1 Web Arc Flash SRL-P	Aluminum rebar hook	9 ft (2,74 m)	100-420 lb (45,3 - 204 kg)	130-310 lb (58,9-140,6 kg)
4200035	CR5 Class 1 Dual Web Arc Flash SRL-P	Steel snap hooks	9 ft (2,74 m)	100-420 lb (45,3 - 204 kg)	130-310 lb (58,9-140,6 kg)
4200036	CR5 Class 1 Dual Web Arc Flash SRL-P	Aluminum snap hooks	9 ft (2,74 m)	100-420 lb (45,3 - 204 kg)	130-310 lb (58,9-140,6 kg)
4200037	CR5 Class 1 Dual Web Arc Flash SRL-P	Steel rebar hooks	9 ft (2,74 m)	100-420 lb (45,3 - 204 kg)	130-310 lb (58,9-140,6 kg)
4200038	CR5 Class 1 Dual Web Arc Flash SRL-P	Aluminum rebar hooks	9 ft (2,74 m)	100-420 lb (45,3 - 204 kg)	130-310 lb (58,9-140,6 kg)

Declaration of conformity

These products been tested in an ISO 17025 accredited laboratory in accordance with all requirements specified by ANSI/ASSP Z359.7.

This product is compliant with the following safety regulations:
ANSI Z359.14-2021 | OSHA 1910.140 & 1926.502 | ASTM F887



ASTM F887 Arc Flash rated

For more information:

+1 (800) 466 6385

customer.service@guardianfall.com



Designed and
tested in the
United States