



HALO-EDGE

Self-Retracting Lifeline

The Halo-Edge Class 2 Self-Retracting Lifeline is part of Guardian's strongest lineup of SRLs in the industry. This anchored Class 2 SRL is recognized throughout the industry for its superior performance. It has evolved over the years to incorporate the features workers want the most and is the go-to SRL for leading edge applications in multiple industries.

Class

2

Anchor above
or below dorsal
D-ring

**HEIGHT SAFETY.
SIMPLIFIED.**

guardianfall.com



HALO-EDGE

Self-Retracting Lifeline



Class

2

Anchor above
or below dorsal
D-ring



10925



Suitable for
LEADING EDGE

Se puede utilizar en aplicaciones borde expuesto

Key features & benefits

Swivel top connection point

Swivels 360 degrees to ensure the device remains in the best orientation during use and also helps prevent lifeline snagging or tangling. Double locking carabiner included.

All metal housing

Heavy Duty & durable for long lasting use in the toughest applications

QR code enabled labels

Easy access to product information

Rubber lifeline stopper

Doubles as a convenient hand-grip

Steel cable lifeline

Resists cuts and abrasions

Guardian shock pack cover

Helps increase product longevity and protect safety labeling

Fall-indicating swivel snap hook

Shows if SRL has been exposed to an impact

Specifications

User weight range (including clothing, tools, & equipment)

ANSI (LE use) | 130-310 lb

OSHA (Non-LE use) | 100-420 lb

Max. Arrest Force | 1,800 lb

Avg. Arrest Force | 1,350 lb

Materials | Aluminum, stainless steel, galvanized steel, rubber

Non-LE use (Anchor at or above dorsal D-ring)

Max. Arresting Distance | 42 in

Max. Allowable Free Fall | Not Permitted

Min. Fall Clearance: 7 ft

LE Use (Anchor below dorsal D-ring)

Min. Setback Distance from Edge | 0 ft

Max. Arresting Distance | 8 ft 6 in

Max. Allowable Free Fall | 5 ft

Min. Fall Clearance: 17 ft

Declaration of conformity

This product has been tested in an ISO 17025 certified laboratory in accordance with all requirements specified by ANSI Z359.7.

This product conforms with the following safety regulations and consensus standard:

OSHA 1910.140 & 1926.502 | ANSI Z359.14

For more information:

+1 (800) 466 6385


info@guardianfall.com



Designed and
tested in the
United States

HALO-EDGE

Self-Retracting Lifeline



Part numbers	Description	Hook type	Length	User Weight Range
10920	Halo-Edge SRL, Cable, Class 2	Steel swivel snap hook	20'	See specifications
10922	Halo-Edge SRL, Cable, Class 2	Steel swivel snap hook	25'	See specifications
10925	Halo-Edge SRL, Cable, Class 2	Steel swivel snap hook	30'	See specifications

Declaration of conformity

This product has been tested in an ISO 17025 certified laboratory in accordance with all requirements specified by ANSI Z359.7.

This product conforms with the following safety regulations and consensus standard:
OSHA 1910.140 & 1926.502 | ANSI Z359.14

For more information:

+1 (800) 466 6385
info@guardianfall.com



Designed and
tested in the
United States