




# VELOCITY CABLE SRL

Self-Retracting Lifeline

This Class 1 SRL is both durable and lightweight to meet the demands of workers who require a straightforward, no-nonsense cable lifeline SRL.



**HEIGHT SAFETY.  
SIMPLIFIED.**

[guardianfall.com](http://guardianfall.com)



# VELOCITY CABLE SRL

Self-Retracting Lifeline



Class

1

Anchor at or  
above dorsal  
D-ring



42003

## Key features & benefits

### Swivel top connection point

Swivels 360 degrees to ensure the device remains in the best orientation during use and also helps prevent lifeline snagging or tangling. Double locking carabiner included.

### Thermoplastic housing

Super lightweight and durable for long-lasting use in the toughest applications

### Rubber lifeline stopper

Doubles as a convenient hand-grip

### Steel cable lifeline

Resists cuts and abrasions

### Fall-indicating swivel snap hook

Shows if SRL has been exposed to an impact

## Specifications

### Class 1 SRL (ANSI Z359.14-2021)

**Average Arrest Force** | 1,350 lb (6 kN)

**Maximum Arrest Force** | 1,800 lb (8 kN)

**Maximum Arrest Distance/Deceleration** |  
3 ft 6 in (1,07 m)

**Fall Free** | Not Permitted

**Minimum Fall Clearance Requirement** |  
7 ft (2,13 m)

**Self-Retracting Device Type (Z359.14)** | SRL

**Materials** | 3/16 in (4,76 mm) galvanized steel cable, zinc plated steel, aluminum, polyolefin, polyester, rubber

## Hook options



Steel swivel snap hook

| Part number(s) | Description           | Hook type              | Length         | OSHA User Weight Range     | ANSI User Weight Range     |
|----------------|-----------------------|------------------------|----------------|----------------------------|----------------------------|
| 10950          | Velocity SRL, Class 1 | Steel swivel snap hook | 10 ft (3,0 m)  | 100 - 420 lb (45 - 190 kg) | 130 - 310 lb (59 - 140 kg) |
| 42000          | Velocity SRL, Class 1 | Steel swivel snap hook | 16 ft (4,8 m)  | 100 - 420 lb (45 - 190 kg) | 130 - 310 lb (59 - 140 kg) |
| 42001          | Velocity SRL, Class 1 | Steel swivel snap hook | 20 ft (6,1 m)  | 100 - 420 lb (45 - 190 kg) | 130 - 310 lb (59 - 140 kg) |
| 42002          | Velocity SRL, Class 1 | Steel swivel snap hook | 30 ft (9,1 m)  | 100 - 420 lb (45 - 190 kg) | 130 - 310 lb (59 - 140 kg) |
| 42003          | Velocity SRL, Class 1 | Steel swivel snap hook | 50 ft (15,2 m) | 100 - 420 lb (45 - 190 kg) | 130 - 310 lb (59 - 140 kg) |

## Declaration of conformity

This product has been tested in an ISO 17025 accredited laboratory in accordance with all requirements specified by **ANSI Z359.7**

This product is compliant with the following safety regulations and consensus standard:  
**OSHA 1910.140 & 1926.502 | ANSI Z359.14-2021**

For more information:

**+1 (800) 466 6385**

**info@guardianfall.com**



Tested in the  
**United States**