



Test Report OSHA Verification

6305 S 231st Street
Kent, WA 98032
800-466-6385

Test Report Number: 2021120311329
Job Number: Qualification 434
Product SKU#: 11329
Product Type: Vertical Lifeline Assembly
Product Description: VL58-25 / 25' with Polydac Rope, snaphook at one end
Testing Standard: OSHA 1910.140, OSHA 1926.502
Dates of Manufacture: 8/16/2019
Date(s) of Testing: 5/01/2019

VERIFICATION TESTING

<u>Test Description</u>	<u>Test Date</u>	<u>Clause/Section</u>	<u>Result</u>
Static Strength	5/01/2019	OSHA 1910.140(c)(4) OSHA 1926.502(d)(9)	Pass

This test report covers these additional products:

11330, 11331, 11332, 11333, 11334, 11335, 11352

Please contact quality@guardianfall.com for signed report.

Test Equipment		
Equipment	Model	Serial
Load Cell	1220ACK-25K-B	367976A

Mandatory/Non-Mandatory Regulatory Requirements		
OSHA 1910.140 (c)(4)	Lanyards and vertical lifelines must have a minimum breaking strength of 5,000 pounds (22.2 kN).	Meets or Exceeds
OSHA 1926.502 (d)(9)	Lanyards and vertical lifelines shall have a minimum breaking strength of 5,000 pounds (22.2 kN).	Meets or Exceeds

Static Strength <i>requirements per 1910.140(c)(4) & 1926.502(d)(9)</i>	
Sample # 01	
Static Load Applied (>5,000 lb)	5040.78
Specimen Successfully Arrested Load?	Yes
Result/Assessment	Pass

Static Strength <i>requirements per 1910.140(c)(4) & 1926.502(d)(9)</i>	
Sample # 02	
Static Load Applied (>5,000 lb)	5054.28
Specimen Successfully Arrested Load?	Yes
Result/Assessment	Pass

Static Strength <i>requirements per 1910.140(c)(4) & 1926.502(d)(9)</i>	
Sample # 03	
Static Load Applied (>5,000 lb)	5057.71
Specimen Successfully Arrested Load?	Yes
Result/Assessment	Pass

Notes